

HS8134 Enclosure

HIGH SECURITY, INDOOR, CEILING MOUNT

Product Features

- Low Cost
- Indoor or Outdoor (Moderate Environment) Applications
- Steel (HS8134) Construction
- Adjustable Camera Mount
- Mounts Directly to Ceiling
- Attractive, Rugged Powder Coat Finish
- Single Tamper-Proof Screw Provides Quick Access and Increased Security




HS8134

The **HS8134** is a high-security ceiling mount enclosure designed for applications requiring maximum protection from vandalism. The **HS8134** is constructed from heavy-gauge steel for high damage resistance.

The **HS8134** features a hinged lower cover that swings down to allow easy access to the camera and lens. The removable camera mount can be easily positioned for various viewing angles, and conduit knockouts allow cabling to be delivered from the wall (either side) or ceiling.

There is no exposed mounting hardware securing the **HS8134** to its mounting surface. Opening the enclosure can only be accomplished with a specially designed tool (included), eliminating the possibility of the enclosure being opened by unauthorized persons. An impact-resistant Lexan® window is supplied with the enclosure.

The **HS8134** is also ideal for use in outdoor applications such as parking garages or other applications offering protection from environmental elements.



NOTE: VALUES IN PARENTHESES ARE CENTIMETERS;
ALL OTHERS ARE INCHES.



C1466 / REVISED 10-02

U.S. Patent #403,340, #6,019,524

International Standards
Organization Registered Firm;
ISO 9001 Quality System



TECHNICAL SPECIFICATIONS

MODEL

HS8134 High-security enclosure constructed from heavy gauge steel. High damage resistance

MECHANICAL

Enclosure Mounting	Four 0.25-inch (0.63 cm) holes on mounting surface
Camera Mounting	Removable, adjustable camera mount
Maximum Camera and Lens Size	Accepts camera and lens combinations* up to: 3.50" H x 3.00" W x 9.75" L (8.89 x 7.62 x 24.77 cm)
Viewing Window HS8134	0.50-inch (12.7 mm) thick Lexan®
Viewing Window Area	3.25" W x 4.75" H (8.25 x 12.07 cm)
Cable Entry	Three 0.875-inch (2.22 cm) diameter knockouts; will accept 0.5-inch (1.27 cm) conduit fitting. One each on flat mounting surface and sides of the enclosure
Security	Tamper-resistant screw (hollow Allen wrench supplied)

*Assumes lens is fully extended.

GENERAL

Construction HS8134	10 gauge CRS, 0.134-inch (3.40 mm)
Finish	Gray polyester powder coat
Environment	Indoor or outdoor (in covered or protected environment)
Unit Weight HS8134	4.15 lb (1.88 kg)
Shipping Weight HS8134	5 lb (2.27 kg)

CERTIFICATIONS/RATINGS/PATENTS

- Meets NEMA Type 1 standards
- U.S. Patents 403,340 and 6,019,524



Pelco, Inc. Worldwide Headquarters:
Fresno, California USA
USA & Canada Tel: (800) 289-9100 • FAX: (800) 289-9150
International Tel: +1 (559) 292-1981 • FAX: +1 (559) 348-1120
www.pelco.com

Pelco and the Pelco logo are registered trademarks of Pelco, Inc.
Lexan is a registered trademark of the General Electric Company.
Product specifications and availability subject to change without notice.
©Copyright 2002, Pelco, Inc. All rights reserved.