

IDM4012SS & IDM4012SS-SW Mount

WALL MOUNT, STAINLESS STEEL, FOR SPECTRA® SPECIALTY DOMES

Product Features


- For Use with Spectra® Series Specialty Domes
- Can Also Be Used with Other Pendant Domes using 1.5-inch NPT Threaded Pipe for Mounting
- Constructed of Type 304 Stainless Steel
- Mounts Directly to Vertical Load-Bearing Surface for Wall Mount Applications
- Supports up to 75 Pounds (34 kg)
- Includes Cable Feedthrough Hole



The **IDM4012SS** wall mount is designed specifically for the Stainless Steel and Pressurized Spectra® Series Dome Systems (Spectra III™ or newer models). The mount is constructed of type 304 stainless steel with a gray or white polyester powder coat finish making it ideal for harsh environmental installations.

IDM4012SS can be attached directly to any vertical load-bearing surface and is designed to support up to 75 pounds (34 kg). Conduit accesses are available through the back mounting plate or through the bottom of the mount where a flexible metal conduit fitting can be installed. A gasket is provided for the back mounting plate to protect the interior of the **IDM4012SS**.

The mount is threaded for a 1.5-inch NPT pipe and is compatible with any Spectra® Series pendant backbox.



NOTE: VALUES IN PARENTHESES ARE CENTIMETERS;
ALL OTHERS ARE INCHES.



TECHNICAL SPECIFICATIONS

MODEL

IDM4012SS	Wall mount with cable feedthrough and conduit access holes for use with Spectra® Stainless Steel and Pressurized dome systems. Painted Pelco Light Gray
IDM4012SS-SW	Wall mount with cable feedthrough and conduit access holes for use with Spectra® Stainless Steel and Pressurized dome systems. Painted Pelco White RAL 9003

GENERAL

Construction	Type 304 stainless steel
Finish	Pelco Light Gray or White RAL 9003 polyester powder coating
Environment	Indoor/outdoor
Mounting Method	Secure with four stainless steel 5/16-inch fasteners (not supplied)
Cable Entry	Two holes on the mounting plate for conduit access and one hole on the bottom of the mount for conduit access
Maximum Load	75 lb (34 kg)
Unit Weight	4.9 lb (2.22 kg)
Shipping Weight	7.0 lb (3.17 kg)

OPTIONAL MOUNT ADAPTERS

SM-PA402-2115	Stainless pole adapter painted Pelco Light Gray
SM-PA402SW-2115	Stainless pole adapter painted Pelco White RAL 9003
IWM-MKIT	Marine Kit